

Granville Hypalube C2/C3 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville Premium C2/C3 is a fully synthetic low SAPS engine oil which is suitable for use in certain vehicles that have exhaust after treatment devices fitted.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3 & C2
API: SN/CF

PRODUCT BENEFITS

- * Fully Synthetic
- * Low SAPS
- * Suitable for use with exhaust after treatment devices

PRODUCT USAGE

Use as recommended by the engine manufacturer where this grade and specification of engine oil is required

DOSAGE INFORMATION

As per the manufacturers recommendations

STORAGE INSTRUCTIONS

Store upright and sealed in a cool dry place out of the reach of children

SHELF LIFE

5 years from date of manufacture



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0825	5020618008255
5 Litre	0826	5020618008262
20 Litre	0823	5020618008231
199 Litre	0829	5020618008293



Granville Hypalube C2/C3 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

SPECIFICATION INFORMATION

Recommended by Granville Oil & Chemicals Ltd for the following applications:

ACEA: C2/C3

API: SN/CF

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Flammability	: Non flammable

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	12.3
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			70.7
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				173

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

